## RDER FORM Classicroc ORDER e: roofsales@ultraframe.co.uk QUOTE e: quotes@ultraframe.co.uk New Build Replacement Project **PLAN VIEW** ACCOUNT No. Company Name Order Number ..... JOB REFERENCE ..... Company Contact ..... Telephone No. ••••• Email Delivery Address ••••• ••••• **POSTCODE** Delivery Date Req FRONT ELEVATION **Quotation Ref** ..... **CRITICAL INFORMATION** \*Required for structural snow / wind loading \*Site Postcode Roof Pitch (°) ••••• Roof height restriction \_\_\_\_\_ Frame width ..... **CUSTOMER NOTE: Please carefully read the** insulated perimeter pelmet design guide before filling in order details. HOW TO PLACE AN ORDER FOR **CLASSIC ROOF: LEFT ELEVATION RIGHT ELEVATION** 1. Sketch plan & elevations. (If necessary, attach photos of existing property. Indicate on drawings if any part of project is existing). 2. Mark and caption the positions of all walls, brick piers, windows/doors, cut outs / intrusions. 3. Mark the preferred positions of any roof

Job No.:3598

Please sign and return to p1 of 2 roofsales@ultraframe.co.uk SIGNED DATE

windows (vents)

 Upon placement of your Classic Roof order, an order confirmation is generated which must be signed and emailed back.

## ORDER FORM



JOB REFERENCE By Ultraframe							
ROOF COLOUR	White	Deeplas	Mahogany	Light Oak	Rosewood	Bespoke RAL/BS (	Colour
External						·	
Internal							
INTERNAL PELMET (when internal pelmet specified)							
□ Specify with this order □ Upgrade with retro fit □ Standard Width (300-600mm) □ Other (600-1200mm)							
Original roof job no. if applicable:						Please state (mm):	
ROOF INFORMATION CENTRAL LIGHTING PANEL							
☐ On Fascia* ☐ Below Fascia ☐ Full Height Walls						☐ Please add	
If fitting to a bungalow please indicate Soffit Depth						DOWNPIPE	
N.B. If order is retro fit then option of <b>on fascia</b> is the only option available.							
CORNICE						CONSERVAFLASH	BAR UNDERCLADDINGS
Style 1 Tier	2 Tier	3 Tier	Curved			Soaker Only	Standard Decorative
Colour White	e Matt G	rey Deepl	as RAL/BS	Colour	•••••••••••••••••••••••••••••••••••••••	Yes	Standard SQ Edge
TOP CAPPINGS TIE BARS EAVES BEAM FASCIA CLADDING							
□ Dome (PVCu) □ White Tie Bar □ Standard (VAAAH) □ 'V' Groove PFTB (Default on glazed roofs & pelmet)							glazed roofs & pelmet)
☐ Aluminium ☐ TBRK (If possible)			☐ Structural (SEB) ☐ Ultraselect SFB (With tapestry infill (SFT003)			ry infill (SFT003) White only)	
☐ Bevel (PVCu)	Brass	Gable beam One piece decorative fascia DFT (All roof colours as above (MUST be used with Cornice)					
			If using SEB please	e indicate span			
and location of doors on drawing.  GLASS OPTIONS - warm edge spacer							
Conservaglass	☐ Ultra ☐ Bror	a86 Blue aze 4S	☐ Ultimate Blu☐ Std Blue		ie 4S d Neutral	☐ Neutral 4S ☐ Std Aqua	☐ Aqua 4S ☐ Std Bronze
Celsius	Cels	ius One	☐ Celsius Elite	e 🗆 Cels	sius Clear		
POLYCARBONATE UNGLAZED							
Size 25mr	n 🗌 35mm					Polycarb	] 25mm
Colour Clear	Opal	Bronz	e 🗌 Bronze /	Opal  H	eatguard / Op	al Glass	] 24mm
ROTABOND SEALANT - MS POLYMER							
☐ White (NCGS001W) ☐ Black (NCGS001B) No. Tubes Req:							
ROOF VENTS AND MECHANISM (mark plan)							
Brass Manual Spindle Manual Spindle and pole Manual Spindle and telescopic pole							
Chrome Manual Spindle Manual Spindle and pole							
<ul> <li>□ Electric motor with digital thermostat and rain sensor</li> <li>□ Electric motor and rocker switch</li> <li>□ Electric motor with radio and remote control</li> <li>□ Electric motor with thermostat (AVTD002)</li> <li>□ Electric without switch/thermostat (Motor only)</li> </ul>							
DECORATION	·	G. alaa		□ <b>5</b> .		laasia	uman fila
Cresting Renai		Tudor Sceptre	☐ Elizabethan☐ Ball	☐ Baroque		_	v profile Aluminium v profile Aluminium
ANCILLARY EXTRAS							
Please refer to the Cl		Guide.					
							Job No.:3598

Please sign and return to

DATE \_\_\_\_\_

p2 of 2